

# MINI COWL



The MINI Cowl is a small cowl/terminal in GRP which can be used to cap ventilation apertures that don't require a big free-area or need a large up-stand. Suitable for a wide range of applications including capping vent stacks, and smaller ventilation jobs. The units provide easy connectivity with conventional duct fittings.

The basic (stocked) model is a smaller version of our RA 200/250. It has a base dim of 300mm and can be used with ducts up to 200mm.

Other versions are available to order which can be used with the below listed S&P and Systemair Centrif fans. These units are efficient running at an airflow of approximately 100l/sec.



Required upstand size 290 x 290 overall.

		<b>Max Internal (mm)</b>	<b>Free Area</b>	<b>Fan</b>
Mini 1	Vent	300	0.0284m <sup>2</sup>	na
Mini 1 L2	Vent	375	0.0123m <sup>2</sup>	na
Mini 2	S&P	375	suit Fan	Vent 125LK
Mini 3	SA	375	suit Fan	K125V
Mini 4	SA	375	suit Fan	KV125XL

For more information, contact us at:

Fairhaven H&V Services Ltd  
3 Glenavy Road  
Moir  
Craigavon  
Co. Armagh  
BT67 0LT  
T: 02892 611648  
E: sales@fairhavenltd.co.uk